



AC 4-wire, 20...250V
 DC 4-wire, 10...300V
 AC rated operational current, $\leq 400\text{mA}$
 DC rated operational current, $\leq 300\text{ mA}$

2 x Normally Open Contacts

S02 - Closed
 S01 - Open

DESCRIPTION Wiring Diagram for Inductive Sensor Switch		NOTICE: THIS DRAWING INCLUDES THE DESIGN AND PRINCIPLES DISCLOSED AND IS THE SOLE PROPERTY OF UNITORQ AND ITS AFFILIATES. IT SUBMITTED WITH THE UNDERSTANDING THAT IT IS NOT TO BE REPRODUCED, NOR COPIED IN WHOLE OR IN PART, NOR LOANED OR OTHERWISE COMMUNICATED TO ANY THIRD PARTY, NOR USED IN ANY MANNER DETRIMENTAL TO THE INTERESTS OF UNITORQ OR ANY OF ITS AFFILIATES WITHOUT THE EXPRESSED WRITTEN CONSENT OF UNITORQ. ACCEPTANCE OF THIS DRAWING WILL BE CONSTRUED AS AN AGREEMENT TO THE ABOVE.				2150 Boggs Road, Suite 410 DULUTH, GEORGIA U.S.A. 30096 Ph: 770-446-7074 Fax: 770-447-1825 www.unitorg.com							
PRODUCT:	Wiring Diagram	PART NUMBER:		SALES DRAWING NUMBER:		DWN BY:	HP	DATE:	5/27/2025	SCALE:		REV.	0